



**20⁺ Years
Production
Forging Experience**



Product Catalogue



Yancheng Cross machinery manufacture Co., Ltd

Product Catalog

Mini & Small Excavator

12 Series Excavator

QH12, QH12R, L12, L12R, H12, QS12R 01

13 & DM Series Excavator

DM12-C, DM12X-C, DM13-C, DM13X-C,
H13R, QH13R 02

15 & KU Series Excavator

H15, KU12, KU15, KU18, KU18E, KU20, KU23,
KU25, KU35, KU45 03-05

UF & J Series Excavator

25UF, 40UF, 65UF, J-18K, J-20K, J-35K, J-45K 06-08

NT & STE Series Excavator

NT18, NT30, NT45, NT-B35, NTB45U-C, STE30SR,
STE35SR, STE45SR 08-09

Other Series Excavator

NR12, QH18KP-C, QH18KPS-C, QK16R, QK18KXS-C,
QK18RXS-C, DY14, DY16, DJ14, CFG12, GG35,
GG45, GN35E, KH16R, TZ60, XC14, XE55, XE60 09-11

Excavator Attachment

AGT-EXFM81, AGT-EXRT046, AGT-EXAB56, AGT-EXFLM115,
AGT-EXRC54, 12EX-LD24B, 12EX-WD24B, 12EX-WD20B,
12EX-WD40B, 12EX-WD15B, 12EX-WD08B, 12EX-WD47B,
12EX-PZ20, 12EX-WD08, 12EX-WD16, 12EX-WD20,
12EX-WD24, 12EX-HYMZJ, 12EX-STQ, 12EX-MZJ,
12EX-ATHK, STE35-HYMZJ, 12EX-BKD23, 12EX-QXD23,
12EX-QXD32, 12EX-QXD39.4, 12EX-HYMZJ II, 12EX-XZZMQ,
12EX-ZMQ, 12EX-XZBB, 12EX-WD32B, 12EX-WD10,
12EX-WD12, 12EX-WD15, 12EX-RC, 12EX-AGR,
12EX-200Adriil, 12EX-200Bdrill, 12EX-250Adriil,
12EX-250Bdrill, 823SS-PF, 12EX-HMZJ, 12EX-300Adriil,
12EX-300Bdrill, M-RC, STE35-HK, 12EX-AGR(C),
GQDA-3PT, 12EX-ZG, 2EX-HMR, 12EX-HM, 12EX-HK 15-20

Skid Steer Loader

23 Series Skid Steer Loader

CBT23, CRT23, KBT23, KTT23, LBT23, LRT23 12

Other models Loader

W938, W948, W958, JC80, JL50, JL80, TK35,
TC80, TL80, T35A, T60A, T50A, LGE08, LGE06,
DY1150, H190, WS100 13-14

Skid Steer Attachment

SSBX42S, SSBGS060, SPA84, ECSSTR072, GB66-SS,
SSEFGC175, SSRC72, HDRC72, HFRC, HCRC, BDRC48,
SSVR72, ECSSCT72, SSCM53, SSBM72, SSAB72,
SSECAG-Y, Stump Grinder, Hydraulic Grapple, BH01,
SSHH-680A, SSHH-750A, PD680-PZ, SSHH-750A, SSSCR72,
ECSSSTG200, ECSSLR72, ECSSRB, SSFM81, SSDFM60,
SSSG72, 4IN1BCT, SSDH-5, SSSB165, Wood Cleaver,
Stone Bucket, Snow Blower, Bucket Mixer, Digger,
Backhoe, M-BK32, M-CT, M-HCB, M-AG, M-DRG,
M-BKM, M-HMR, M-AB, M-BM 21-26

Tractor Attachment: Rotary tiller

TLM, TX, TW, TS, TA, KK, TH, TU, RXG, TB, EFM,
BCRL, EFGC, EFGCH, EFME, MFZ, SB, BB 27-28

Other Industrial Products

Automotive maintenance machinery, Industrial tents,
Electric forklift, Traffic cone, Hot water cleaning machine,
Seeder, Wood crusher, Busy at both ends, Guardrail 29-31



Model Information Configuration Status √Standard, △Optional, ×None Abnormal data in red		12 SERIES					
		H12	QH12	QH12R	L12	L12R	QS12R
Basic Performance Parameters	Working Weight(kg)	855	830	830	900	900	845
	Bucket capacity(m³)	0.025	0.03	0.03	0.03	0.03	0.025
	Travel speed low/high speed(Km/h)	0-1.8	0-1.8	0-1.8	0-1.8	0-1.8	0-1.5
	Climbing ability(%)	30	30	30	30	30	30
	A Maximum Digging Height(mm)	2550	2550	2550	2750	2750	2350
	B Maximum Unloading Height(mm)	1780	1780	1780	1960	1960	1600
	C Maximum Digging Depth(mm)	1644	1644	1644	1630	1630	1300
	E Max. digging radius(mm)	2960	2960	2960	2900	2900	2460
	Side Swing	×	×	×	×	×	×
	Side Swing Angle (L/R)	×	×	×	×	×	×
Body	undercarriage expansion	×	×	×	×	×	×
	J Overall Length(mm)	2240	2895	2895	2200	2200	2430
	K Overall Width(mm)	958	958	958	930	930	720
	L Overall Height(mm)	2200	2200	2200	2250	2250	1390
	Bulldozer Width/Height	907/210	907/400	907/400	180/210	180/210	907/400
Engine	Engine Brand	B&S	B&S	Rato	Koop	Rato	Rato
	Engine Model	13.5HP	13.5HP	R420D	KD192F	R420D	R420D
	Max. power(Kw)	9.8	9.8	8.6	7.6	8.6	8.6
	Max. speed(rpm)	3600	3600	3600	3600	3600	3600
	Cylinders	1	1	1	1	1	1
	Cooling method	fan cooling	fan cooling	fan cooling	water cooling	fan cooling	fan cooling
	Engine oil change quantity(L)	1.1	1.1	1.1	1.1	1.1	1.1
	Fuel Type	Gasoline	Gasoline	Gasoline	Diesel	Gasoline	Gasoline
	Fuel Grade	92#	92#	92#		92#	92#
Hydraulic system	Theoretical fuel consumption(L/h)	0.5-1.2	0.5-1.2	0.5-1.2	1-1.6	0.5-1.2	0.5-1.2
	Main pump type/model	gear pumps/06	gear pumps/06	gear pumps/06	gear pumps/06	gear pumps/06	gear pumps/06
	Main pump brand	(Tianjin Xingzou)	(Tianjin Xingzou)	(Tianjin Xingzou)	(Tianjin Tianji)	(Tianjin Tianji)	(Tianjin Xingzou)
	Rated set pressure(Mpa)	23.5	16	16	23.5	23.5	16
	Maximum flow rate of main pump(L/min)	21.6	21.6	21.6	21.6	21.6	18
	Multi-way valve	8 manually operated multi-way valves	8 manually operated multi-way valves	8 manually operated multi-way valves	8 manually operated multi-way valves	8 manually operated multi-way valves	8 manually operated multi-way valves
	Brand of Multi-way valve	(Hua Sheng)	(Tai Heng)	(Tai Heng)	(Bei Fang)	(Bei Fang)	(Tai Heng)
	Rated Set Pressure(Mpa)	16	16	16	16	16	16
	Hydraulic Linear Motor type	BM6-310	BM6-315	BM6-315	BM6-310	BM6-310	BM6-315
	Linear Motor Brand	(Li Yuan)	(Li Wo)	(Li Wo)	(Li Yuan)	(Li Yuan)	(Li Wo)
Excavator tracks	Hydraulic Servo Motor type	BM2-250	BM2-315	BM2-315	BM2-250	BM2-250	BM2-315
	△-Rubber (bandwidth*pitch*number of sections)	180*72*37	180*72*37	180*72*37	180*72*37	180*72*37	180*72*37
Configuration	Cab	×	×	×	×	×	×
	Roof	√	√	√	√	√	√
	Handrail	√	√	√	√	√	√
	Thumb Clip	√	√	√	√	√	√
	Counterweight	√	√	×	√	√	√
	Tensioning Forms	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
	Air Conditioning	×	×	×	×	×	×
Fuel tank	Fuel tank(L)	6.6	6.6	6.6	10	10	6.6
	Hydraulic oil tan (L)	12	12	12	16	16	12



Model:AGT-DM12-C 31.03.001.012.013

Model:AGT-DM12X-C 31.03.001.012.019



Model:AGT-DM13-C 31.03.001.013.005

Model:AGT-DM13X-C 31.03.001.013.006



Model:AGT-H13R 31.03.001.013.002

Model:AGT-QH13R 31.03.001.013.002

Model Information Configuration Status √Standard, △Optional, -None Abnormal data in red		DM SERIES & 13 SERIES					
		DM12-C	DM12X-C	DM13-C	DM13X-C	H13R	QH13R
Basic Performance Parameters	Working Weight(kg)	870	830	940	900	900	960
	Bucket capacity(m³)	0.025	0.03	0.03	0.03	0.025	0.03
	Travel speed low/high speed(Km/h)	0-1.8	0-0.2	0-0.2	0-0.2	0-1.8	0-1.8
	Climbing ability(%)	30	30	30	30	30	30
	A Maximum Digging Height(mm)	2670	2795	2795	2795	2550	2560
	B Maximum Unloading Height(mm)	1900	1863	1863	1863	1780	1800
	C Maximum Digging Depth(mm)	1764	1684	1684	1684	1644	1693
	E Max. digging radius(mm)	3080	3112	3112	3112	2960	3060
	Side Swing	△	√	√	√	×	×
	Side Swing Angle (L/R)	30/30	30°	30°	30°	×	×
Body	undercarriage expansion	×	×	×	×	×	×
	J Overall Length(mm)	2260	2738	2738	2738	2240	2925
	K Overall Width(mm)	958	935	935	935	928	958
	L Overall Height(mm)	2200	2209	2209	2209	2190	2422
Engine	Bulldozer Width/Height	907/359	907/210	907/210	907/210	907/210	907/400
	Engine Brand	B&S	B&S	B&S	B&S	Rato	Rato
	Engine Model	13.5HP	13.5HP	13.5HP	13.5HP	R420D	R420D
	Max. power(Kw)	9.8	9.8	9.8	9.8	8.6	8.6
	Max. speed(rpm)	3600	3600	3600	3600	3600	3600
	Cylinders	1	1	1	1	1	1
	Cooling method	fan cooling	fan cooling	fan cooling	fan cooling	fan cooling	fan cooling
	Engine oil change quantity(L)	1.1	1.1	1.1	1.1	1.1	1.1
	Fuel Type	Gasoline	Gasoline	Gasoline	Gasoline	Gasoline	Gasoline
Hydraulic system	Fuel Grade	92#	92#	92#	92#	92#	92#
	Theoretical fuel consumption(L/h)	0.5-1.2	0.5-1.2	0.5-1.2	0.5-1.2	0.5-1.2	0.5-1.2
	Main pump type/model	gear pumps/06	gear pumps/06	gear pumps/06	gear pumps/06	gear pumps/06	gear pumps/06
	Main pump brand	(Tianjin Xingzou)	(Tianjin Xingzou)	(Tianjin Xingzou)	(Tianjin Xingzou)	(Huaheng/Tongrun)	(Tianjin Xingzou)
	Rated set pressure(Mpa)	23.5	16	16	16	23.5	16
	Maximum flow rate of main pump(L/min)	21.6	21.6	21.6	21.6	21.6	21.6
	Multi-way valve	8 manually operated multi-way valves	8 multi-way valves	8 multi-way valves	8 multi-way valves	8 manually operated multi-way valves	8 manually operated multi-way valves
	Brand of Multi-way valve	(Bo Xin) / (Hua Sheng)	(Bei Fang)	(Bei Fang)	(Bei Fang)	(Hua Sheng)	(Tai Heng)
	Rated Set Pressure(Mpa)	16	16	16	16	16	16
	Hydraulic Linear Motor type	BM6-310	BM6-310	BM6-310	BM6-310	BM6-315	BM6-315
Excavator tracks	Linear Motor Brand	(Li Yuan) / (Jining Songheng)	(Li Yuan)	(Li Yuan)	(Li Yuan)	(Li Yuan)	(Li Wo)
	Hydraulic Servo Motor type	BM2-250	BM2-250	BM2-250	BM2-250	BM2-250	BM2-315
Configuration	△-Rubber (bandwidth/pitch/number of sections)	180*72*37	180*72*37	180*72*37	180*72*37	180*72*37	180*72*37
	Cab	×	×	√	√	√	√
	Roof	√	√	×	×	×	×
	Handrail	√	×	×	×	×	×
	Thumb Clip	√	√	√	√	√	√
	Counterweight	×	×	×	×	√	×
	Tensioning Forms	Mechanical tensioning	Mechanical tensioning	Mechanical tensioning	Mechanical tensioning	Mechanical tensioning	Mechanical tensioning
Fuel tank	Air Conditioning	×	△	△	△	×	×
	Fuel tank(L)	6.6	6.6	6.6	6.6	6.6	6.6
	Hydraulic oil tank (L)	18	18	18	18	12	15



Model:AGT-H15 31.03.001.015.003



Model:AGT-KU12 31.03.001.020.001



Model:AGT-KU15

Model Information Configuration Status ●Standard, ○Optional, -None		15 SERIES	KU SERIES				
		H15	KU12 (SNI0BC-6)	KU15 (SY13JC-6)	KU18 (SY17JN-6P)	KU18E (SY17JC-6-BJ)	KU20 (SY17JN-6P (驾驶室)
Basic Performance Parameters	Weight(kg):	890	850	1250	1550	1520	1620
	Bucket capacity(m³):	0.025	0.022	0.026	0.04	0.04	0.04
	Walking speed Low/High speed(Km/h):	0-1.8	0-1.8	0-2.5	2/3.5	2/3.5	2/3.5
	Gradeability(%):	30	30	25 (30)	58 (30)	58 (30)	58 (30)
	speed of gyration (r/min)	10	11	9.5	9	9	9
	Maximum digging force of the bucket(KN):	6	6.2	11.5	13.8	13.8	13.8
	Maximum digging force of boom(KN):	4	4.5	6	7.5	7.5	7.5
	Maximum excavation height(mm):	2550	2580	3130	3310	3310	3310
	Maximum unloading height(mm):	1780	1830	2173	2370	2370	2370
	Maximum Digging Depth(mm):	1644	2000	1810	2120	2120	2120
	Maximum vertical excavation depth(mm):	1422	1600	1600	1535	1535	1535
	Maximum digging radius(mm):	2960	2850	1411	3640	3640	3640
	Minimum radius of gyration(mm):	1330	1290	3475	1660	1660	1660
	Minimum gyration radius of the tail(mm):	800	750	860	715	715	715
	Maximum lifting height of bulldozer	140	260	155	260	260	260
	Maximum digging height of bulldozer	270	190	264	190	190	190
	side swing	/	○	○	○	○	○
	side swing angle (left-right)	/	60/50	60/50	60/50	60/50	60/50
Size	chassis extension	/	○	○	○	○	○
	Total length(mm):	3040	2600	3100	3300	3300	3300
	Total width(mm):	958	850	1100	1110	1110	1110
	Total height(mm):	2300	2200	2300	2360	2360	2360
	Tread width(mm):	1045	670	920	883	875	883
	Track gauge(mm):	778	490	740	653	695	653
	Bulldozer width/height(mm):	910/230	850/180	1110/155	1120/258	1120/258	1120/258
	Engine Brand:	RAVO	Briggs&Stratton	Kubota	Kubota	Kubota	Kubota
Engine	Engine model:	R500	13.5HP	D722-E4B-SXN-1	D722-E4B-SXN-1	D722-E4B-SXN-1	D722-E4B-SXN-1
	Maximum power(Kw):	12	9.8	10.2	10.2	10.2	10.2
	Maximum Rotation Speed(rpm):	3600	3600	2500	2500	2500	2500
	Number of cylinders:	1	1	3	3	3	3
	Cooling method:	forced air cooling	forced air cooling	water-cooling	water-cooling	water-cooling	water-cooling
	Engine oil change volume(L):	1.2	1.1	3.8	3.8	3.8	3.8
	Fuel type:	gasoline	gasoline	diesel	diesel	diesel	diesel
	Fuel label:	92#	92#	0#	0#	0#	0#
Hydraulic System	Theoretical fuel consumption(L/h):	/	/	/	/	/	/
	Main pump type/model:	gear pump/06+03	gear pump/06	gear pump/08	piston pump/15	gear pump/13	piston pump/15
	Main pump brand:	Tianjin Walking	WanYe	WanYe	BuErYue	WanYe	BuErYue
	Rated set pressure(Mpa):	16	17	17	20	17	21
	Max. flow rate of main pump(L/min):	32.4	21.6	30	35	32.5	35
	multi-way valve:	8-way (4-way pilot +4-way mechanical)	8-way manual multi way valve	8-way manual multi way valve	9-way hydraulic control multi way valve	9-way hydraulic control multi way valve	9-way hydraulic control multi way valve
	Multi way valve brand:	North	Huainan	North	North	Huainan	North
	Rated set pressure(Mpa):	16	17	17	18	16	18
	Walking hydraulic motor type:	BM6-310	BM6-310	BM6-310	LTM02PA	BM6-390	LTM02PA
	Walking Motor Brand:	Liyuan	Olake	Olake	Lakechuan	Olake	Lakechuan
	Motor Displacement:	315	310	310	13+6.2	390	13+6.2
	Rotary hydraulic motor type:	BM2-250	BM2-315	BM5-315	OLD-245	OLD-245	OLD-245
Track	Displacement:	250	315	315	245	245	245
	O-Rubber	○	○	○	○	○	○
	(track width * pitch * number of sections):	180*72*41	180*72*37	180*72*41	230*72*43	230*72*43	230*72*43
configuration	O-Steel	-	-	-	230*72*43	-	230*72*43
	(track width * pitch * number of sections):	-	-	-	-	-	-
	rubber block	-	-	-	-	-	-
	cab	-	-	-	○	○	○
	ceiling	●	●	●	●	●	●
	armrest	●	○	●	●	●	●
	quick hitch	○	○	○	○	○	○
	rake	○	○	○	○	○	○
	log grapple	○	○	○	○	○	○
	ripper	○	○	○	○	○	○
Tank	hammer	○	○	○	○	○	○
	Counterweight	○	●	●	●	●	●
	Tensioning form	Mechanical tensioning	Hydraulic tensioning	Hydraulic tensioning	Hydraulic tensioning	Hydraulic tensioning	Hydraulic tensioning
Tank	air-conditioning	-	-	-	-	-	-
	fuel tank(L):	7	6.6	5.5	17	17	17
	hydraulic tank (L)	12	11	14.5	13	13	13



Model:AGT-KU23



Model:AGT-KU25



Model:AGT-KU35

Model Information Configuration Status ●Standard, ○Optional, -None		KU23 (SY23JN-6PS)	KU25 (SY23JN-6PS驾驶室)	KU35 (SY25JF-6PS (驾驶室))	KU35 (SY25JF-6PS)KU25-2 老款不含驾驶室Without cab	KU45 (SY35YF-6P)
Basic Performance Parameters	Weight(kg):	2100	2200	2580	2480	3515
	Bucket capacity(m³):	0.04	0.04	0.066	0.066	0.09
	Walking speed Low/High speed(Km/h):	2.4/4.2	2.4/4.2	2.4/4.2	2.4/4.2	3.0/4.2
	Gradeability(%):	58 (30)	58 (30)	58 (30)	58 (30)	58 (30)
	speed of gyration (r/min):	7.5	7.5	9.5	9.5	8.5
	Maximum digging force of the bucket(KN):	18.4	18.4	18.4	18.4	26.5
	Maximum digging force of boom(KN):	8.8	8.8	12.5	12.5	17.5
	Maximum excavation height(mm):	3700	3700	3880	3880	4600
	Maximum unloading height(mm):	2500	2500	2550	2550	3175
	Maximum Digging Depth(mm):	2430	2430	2320	2320	2880
	Maximum vertical excavation depth(mm):	1850	1850	1900	1900	2305
	Maximum digging radius(mm):	4100	4100	4140	4140	4965
	Minimum radius of gyration(mm):	1850	1850	1850	1850	2035
	Minimum gyration radius of the tail(mm):	710	710	710	710	790
	Maximum lifting height of bulldozer	340	340	340	340	360
	Maximum digging height of bulldozer	270	270	270	270	340
	side swing	●	●	●	●	●
	side swing angle (left/right)	75/55	75/55	75/55	75/55	75/55
Size	chassis extension	●	●	●	●	-
	Total length(mm):	3730	3730	3850	3850	4485
	Total width(mm):	1280/1440	1280/1440	1300/1500	1300/1500	1550
	Total height(mm):	2240	2240	2380	2380	2440
	Tread width(mm):	910	910	1070	1070	1250
	Track gauge(mm):	680	680	840	840	950
Engine	Bulldozer width height(mm):	1440/280	1440/280	1300/292	1300/292	1550/335
	Engine Brand:	Kubota	Kubota	Kubota	Kubota	Yanmar
	Engine model:	D1105-E4B-CBH-1	D1105-E4B-CBH-1	D1105-E4B-CBH-1	D1105-E4B-CBH-1	3TNV88F-ESSY
	Maximum power(Kw):	14	14	14	14	18.2
	Maximum Rotation Speed(rpm):	2200	2200	2200	2200	2200
	Number of cylinders:	3	3	3	3	3
	Cooling method:	water-cooling	water-cooling	water-cooling	water-cooling	water-cooling
	Engine oil change volume(L):	5.1	5.1	5.1	5.1	6.7
	Fuel type:	diesel	diesel	diesel	diesel	diesel
	Fuel label:	0#	0#	0#	0#	0#
Hydraulic System	Theoretical fuel consumption(L/h):	/	/	/	/	/
	Main pump type/model:	piston pump/18	piston pump/18	load-sensing pump/28	load-sensing pump/28	load-sensing pump/45
	Main pump brand:	BuErYue	BuErYue	Taifeng	Taifeng	Taifeng
	Rated set pressure(Mpa):	21	21	21	21	21
	Max. flow rate of main pump(L/min):	40	40	62	62	99
	multi-way valve:	9-way hydraulic control multi way valve	9-way hydraulic control multi way valve	9-way hydraulic control multi way valve	9-way hydraulic control multi way valve	9-way hydraulic control multi way valve
	Multi way valve brand:	North	North	Taifeng	Taifeng	Taifeng
	Rated set pressure(Mpa):	19	19	20	20	20
	Walking hydraulic motor type:	LTM02PA	LTM02PA	LTM 03CA	LTM 03CA	LTM 03AX
	Walking Motor Brand:	Lakechuan	Lakechuan	Lakechuan	Lakechuan	Lakechuan
Track	Motor Displacement:	13+6.2	13+6.2	18+10	18+10	23+15
	Rotary hydraulic motor type:	OLD-245	OLD-245	OLD-245	OLD-245	LSMN24B-21B
	Displacement:	245	245	245	245	18
	O-Rubber	●	●	●	●	●
	(track width * pitch * number of sections):	230*48*70	230*48*70	250*47*84	250*47*84	300*52.5*84
	O-Steel	●	●	●	●	●
	(track width * pitch * number of sections):	DH90-52-26-230/37L	DH90-52-26-230/37L	DHS90/52-26-250/47L	DHS90/52-26-250/47L	DHS101-68-35-300/43L
	rubber block	○	○	○	○	○
	cab	○	○	○	○	○
	ceiling	●	●	●	●	●
configuration	armrest	●	●	●	●	●
	quick hitch	○	○	○	○	○
	rake	○	○	○	○	○
	log grapple	○	○	○	○	○
	ripper	○	○	○	○	○
	hammer	○	○	○	○	○
	Counterweight	●	●	●	●	●
	Tensioning form	Hydraulic tensioning	Hydraulic tensioning	Hydraulic tensioning	Hydraulic tensioning	Hydraulic tensioning
	air-conditioning	○	○	○	○	○
	fuel tank(L):	28	28	28	28	40
Tank	hydraulic tank (L)	22.5	22.5	22.5	22.5	33



Model:AGT-QS12R



Model:AGT-KU18/KU18E

31.03.001.018.001



Model:AGT-KU20



Model:AGT-XC14



Model:AGT-XE55

31.03.001.060.003



Model:AGT-XE60

31.03.001.060.001



Model:CFG-25UF



Model:CFG-40UF

31.03.001.040.004



Model:CFG-65UF

31.03.0101.030.004



Model:CFG-J-18K



Model:CFG-J-20K



Model:CFG-J-35K



Model:CFG-J-45K



Model:AGT-NT18



Model:AGT-NT30

31.03.001.030.005



Model:AGT-NT45

31.03.001.040.001



Model:AGT-NT-B35



Model:CFG-NTB45U-C

31.03.001.045.050



Model:CFG-STE30SR



Model:CFG-STE35SR



Model:CFG-STE45SR



Model:AGT-NR12



Model:AGT-QH18KP-C



Model:AGT-QH18KPS-C



Model:AGT-QK16R



Model:AGT-QK18KXS-C

31.03.001.018.012



Model:AGT-QK18RXS-C

31.03.001.018.010



Model:AGT-DY14

31.03.001.014.001



Model:AGT-DY16

31.03.001.016.001



Model:AGT-DJ14

31.03.001.014.010



Model:AGT-CFG12



Model:AGT-GG35

31.03.001.035.007



Model:AGT-GG45

31.03.001.045.001



Model:AGT-GN35E

31.03.001.035.008



Model:AGT-KH16R

31.03.001.016.003



Model:RSWG-TZ60



Model:CFG-LBT23 31.03.002.02.02.002.001
Model:CFG-LRT23 31.03.002.02.02.002.002



Model:CFG-KBT23 30.77.01.002
Model:CFG-KTT23 30.77.01.001



Model:CFG-CBT23 31.03.002.02.02.002.003
Model:CFG-CRT23

Model Information Configuration Status √Standard, △Optional, ×None Abnormal data in red		LBT Series		KBT Series		CBT Series	
		LBT23	LRT23	KBT23	KTT23	CBT23	CRT23
Basic Performance Parameters	Working Weight(kg)	880	880	905	905	950	950
	Bucket capacity(m³)	0.15	0.15	0.12	0.12	0.1	0.1
	Travel speed low/high speed(Km/h)	4	4	3	3	4	4
	Climbing ability(%)	25	25	30	30	30	30
	Maximum lifting force (Kg)	200	200	220	220	200	200
	C Maximum working height(mm)	2100	2100	2450	2450	2323	2323
	B Maximum pin height (mm)	1800	1800	1800	1800	2007	2007
	A Maximum unloading height(mm)	1480	1480	1350	1350	1612	1612
	G Loading distance at maximum unloading height (mm)	430	430	840	840	611	611
	H Wheelbase(mm)	760	760	690	690	965	965
	F Ground clearance(mm)	110	110	120	120	203	203
	L Bucket discharge angle	30°	30°	20°	20°	23°	23°
Body	E Bucket width(mm)	1150	1150	812	812	1120	1120
	J/K Overall Length(mm)	2055/2285	2055/2285	2180/2330	2180/2330	2181/2435	2181/2435
	N Overall Width(mm)	1090	1090	820	820	1120	1120
	O Body width(mm)	810	810	810	810	826	826
	D Overall Height(mm)	1270	1270	1420	1420	1383	1383
	M Slewing radius(mm)	1300	1300	1400	1400	1500	1500
Engine	Engine Brand	B&S	Rato	B&S	Rato	B&S	Rato
	Engine Model	23HP	740	23HP	740	23HP	740
	Max. Horsepower(pc)	23	23	23	23	23	27
	Maximum power(Kw)	16.79	16.8	16.79	16.8	16.8	16.8
	Max. speed(rpm)	3600	3600	3600	3600	3600	3600
	Displacement (cc)	627	739.3	627	739.3	627	739
	Cylinders	2	2	2	2	2	2
	Cooling method	fan cooling	fan cooling	fan cooling	fan cooling	fan cooling	fan cooling
	Engine oil change quantity(L)	1.7	1.6	1.7	1.6	1.7	1.6
	Fuel Type	Gasoline	Gasoline	Gasoline	Gasoline	Gasoline	Gasoline
	Fuel Grade	92#	92#	92#	92#	92#	92#
	Theoretical fuel consumption(L/h)	×	×	×	×	×	×
Hydraulic system	Main pump type/model	gear pumps	gear pumps	gear pumps	gear pumps	gear pumps	gear pumps
	Main pump brand	(Tianjin Xingzou)	(Tianjin Xingzou)	(Tianjin Xingzou)	(Tianjin Xingzou)	(Tianjin Xingzou)	(Tianjin Xingzou)
	Rated set pressure(Mpa)	22	22	22	22	22	22
	Maximum flow rate of main pump(L/min)	75.6	75.6	75.6	75.6	75.6	75.6
	Multi-way valve	Two sets (3+2) of manual valves	Two sets (3+2) of manual valves	Two sets of 3 manual valves	Two sets of 3 manual valves	2+2+2	2+2+2
	Brand of Multi-way valve	(Li Xin)	(Li Xin)	(Li Xin)	(Li Xin)	(Li Xin)	(Li Xin)
	Rated Set Pressure(Mpa)	16	16	16	16	16	16
	Hydraulic Linear Motor type	Cycloid hydraulic motor	Cycloid hydraulic motor	Cycloid hydraulic motor	Cycloid hydraulic motor	Cycloid hydraulic motor	Cycloid hydraulic motor
	Linear Motor Brand	(Dan Fusi)	(Dan Fusi)	(Dan Fusi)	(Dan Fusi)	(Dan Fusi)	(Dan Fusi)
	Motor Displacement	350	350	350	350	350	350
Tracks	△-Rubber (bandwidth*pitch*number of sections)	200*72*32	200*72*32	200*72*32	200*72*32	180*72*41	180*72*41
	Wheels	△	△	△	△	△	△
Configuration	Cab	×	×	×	×	×	×
	Roof	×	×	×	×	×	×
	Handrail	√	√	√	√	√	√
	Tensioning Forms	Hydraulic Tensioning	Hydraulic Tensioning	Hydraulic Tensioning	Hydraulic Tensioning	Hydraulic Tensioning	Hydraulic Tensioning
	Air Conditioning	×	×	×	×	×	×
Fuel tank	Fuel tank(L)	18	18	18	18	31	31
	Hydraulic oil tan(L)	30	30	30	30	33	33



Model:CFG-TK35

Skid Steer Loader



Model:CFG-TC80

31.03.002.02.01.005.002

Skid Steer Loader



Model:CFG-TL80

31.03.002.02.01.005.001

Skid Steer Loader



Model:CFG-JL80

31.03.002.01.01.010.002

Skid Steer Loader



Model:WS100

Skid Steer Loader



Model:CFG-JL50

31.03.002.01.01.004.002

Skid Steer Loader



Model:CFG-JC80

31.03.002.01.01.010.003

Skid Steer Loader



Model:CFG-W938/W948/W958

31.03.002.01.01.005.001

31.03.002.01.01.011.001

31.03.002.01.01.012.001

Bridge Loader



Model:LGE06

31.03.002.01.01.001.002

Hydraulic loader



Model:LGE08

31.03.002.01.01.001.003

Hydraulic loader



Model:H190

Hydraulic loader



Model:DY1150

31.03.002.02.01.004.001

Hydraulic loader



Model:AGT-EXFM81 30.62.002.001

EXFM81 Excavator Type Topper
Excavator interface: apolegamy(CAT324D-325D)
Applicable models T: 24-25
Working Width (MM): 1550
Rototilling ground depth(mm): 100
Cutterhead quantity: 39
Working Pressure(MPa): 20Flow(l/min): >110
N.Weight (KG): 940



Model:AGT-EXRT046 30.71.01.003

Excavator Rotary Tiller
Excavator interface: apolegamy(CAT307)
Applicable models T: 6-8
Working width(MM): 1015
plowing Depth(MM): 180
Blade quantity: 20NVeg hK G: 192
Measurement(MM): 1530*750*540Working Pressure(MPa): 10



Model:AGT-EXAB56 30.08.24.01.001

Excavator Angel Broom
Excavator interface: apolegamy(CAT307)
Applicable models T: 6-8 Working width(MM): 1270
Brush blade size(mm): 165*560
Brush blade quantity: 28*2 N.Weight(KG): 194
Measurement(MM): 1800*750*600Working Pressure (MPa): 17.5
Flow(l/min): 32-45



Model:AGT-EXFLM115 30.08.24.01.001

Excavator Flail Mower
Cutting capacity: 4"
Hydraulic flow: 10-16 GPM
Auxiliary pressure: 2900 PSI
Number of knives: 24
Cutting width: 46"
Packing Information
One unit per plywood case



Model:AGT-EXRC54 30.08.02.08.002

Excavator ROTARY CUTTER
Overall Size: 54" x 16.5" x 18"
Cutting Width: 54" Cutting Height: 1 19/32"
Quantity Of Blades: 2 Flow Rating: 16-21 GPM
Max Pressure: 3050psi Weight: 540LB
Apply to 3-8 tons Excavator Fit Caterpillar 306, 307, 308



Model:12EX-LD24B 26.049.009.007

Bucket
-Mainly used for river dredging, clearing water grass, etc.
-Also capable of construction work such as excavation and screening, road maintenance, etc.
-Packaged Weight: 31.9KG
-Packaged Dimensions: 645*460*280mm



Model:12EX-WD24B 26.049.009.008

Bucket
-Wear-resistant material
-Easy installation and operation, safe and reliable
-Suitable for excavating general clay and handling sand, soil, and gravel
-Packaged Weight: 37.8KG
-Packaged Dimensions: 645*460*280mm



Model:12EX-WD20B 26.049.009.009

Bucket
-Wear-resistant material
-Easy installation and operation, safe and reliable
-Suitable for excavating general clay and handling sand, soil, and gravel
-Packaged Weight: 31.5KG
-Packaged Dimensions: 550*460*280mm



Model:12EX-WD40B 26.049.009.010

Bucket
-Wear-resistant material
-Easy installation and operation, safe and reliable
-Suitable for excavating general clay and handling sand, soil, and gravel
-Packaged Weight: 55.5KG
-Packaged Dimensions: 1045*460*280mm



Model:12EX-WD15B 26.049.009.011

Bucket

- Wear-resistant material
- Easy installation and operation, safe and reliable
- Suitable for excavating general clay and handling sand, soil, and gravel
- Packaged Weight: 24.7KG
- Packaged Dimensions: 420*460*275mm



Model:12EX-WD08B 26.049.009.017

Bucket

- Wear-resistant material
- Easy installation and operation, safe and reliable
- Suitable for excavating general clay and handling sand, soil, and gravel
- Packaged Weight: 17.4KG
- Packaged Dimensions: 460*245*275mm



Model:12EX-WD47B 26.049.009.018

Bucket

- Wear-resistant material
- Easy installation and operation, safe and reliable
- Suitable for excavating general clay and handling sand, soil, and gravel
- Packaged Weight: 64.1KG
- Packaged Dimensions: 1245*460*280mm



Model:12EX-PZ20 26.099.031.010

Rake

- The machine has low energy consumption and performs effectively. It is easy to use, safe, and reliable. It is mainly used for deep tilling of land, land clearing, tree root excavation, medicinal herb digging, and stone sieving.
- Packaged Weight: 21.1KG
- Packaged Dimensions: 540*540*200mm



Model:12EX-WD08 30.75.02.01.020

Bucket

- Wear-resistant material
- Easy installation and operation, safe and reliable
- Suitable for excavating general clay and handling sand, soil, and gravel
- Packaged Weight: 24.5KG
- Packaged Dimensions: 540*270*315mm



Model:12EX-WD16 30.75.02.01.040

Bucket

- Wear-resistant material
- Easy installation and operation, safe and reliable
- Suitable for excavating general clay and handling sand, soil, and gravel
- Packaged Weight: 35.3KG
- Packaged Dimensions: 540*470*315mm



Model:12EX-WD20 30.75.02.01.050

Bucket

- Wear-resistant material
- Easy installation and operation, safe and reliable
- Suitable for excavating general clay and handling sand, soil, and gravel
- Packaged Weight: 43.4KG
- Packaged Dimensions: 570*540*315mm



Model:12EX-WD24 30.75.02.01.062

Bucket

- Wear-resistant material
- Easy installation and operation, safe and reliable
- Suitable for excavating general clay and handling sand, soil, and gravel
- Packaged Weight: 46.7KG
- Packaged Dimensions: 675*540*315mm



Model:12EX-HYMZJ 30.75.02.06.003

Hydraulic Thumb Clamp

- The hydraulic thumb clamp is advantageous for grasping small wood, cylindrical objects, and strip-shaped materials in conjunction with the bucket.
- The multi-functional bucket clamp, developed based on the bucket, is capable of both digging and clamping.
- It can be used for stone handling, repairing dams, and other multi-purpose applications, with easy operation.
- Product Weight: 11kg
- Product Dimensions: 510*175*120mm



Model:12EX-STQ 26.099.031.001

Ripper

-Applicable for crushing and splitting hard soil, semi-hard rock, and weathered stone to facilitate excavation with a bucket.
-Packaged Weight: 16.7KG
-Packaged Dimensions: 500*240*180mm



Model:12EX-MZJ

Thumb Clamp

-It has advantages in cooperating with the bucket for grabbing small wood, cylindrical objects, and strip-shaped materials. This multi-functional bucket clamp, developed based on the bucket, is capable of both digging and clamping, making it versatile for tasks such as loading and unloading stones and repairing road dams, offering convenient operation for multiple purposes.
-Product Weight: 9.6KG
-Product Dimensions: 500*165*120mm



Model:12EX-ATHK 30.75.03.002

Quick Coupler

The quick coupler for excavators allows for the rapid installation and switching of various attachments (such as buckets, rippers, hydraulic breakers, and hydraulic shears), expanding the excavator's versatility, saving time, and improving efficiency.
-Digital Model Weight: 14.2KG
-Digital Model Dimensions: 250*200*180mm



Model:STE35-HYMZJ 30.75.02.06.005

Hydraulic thumb clamp

This equipment can be adapted to 3-5 ton excavators. It controls the expansion and contraction of hydraulic cylinders through the excavator's hydraulic output, allowing it to work in coordination with the bucket to grasp materials, preventing material dropping and enabling the free grabbing and releasing of materials.
-Product Weight: 70.2KG
-Product Dimensions: 625*310*240mm



Model:12EX-BKD23 30.75.02.01.001

Shell Bucket

-Loading and handling operations for coal, sand, gravel, ores, and sludge
-Particularly suitable for excavation and loading in ditches or confined spaces
-Packaged Weight: 74.3KG
-Packaged Dimensions: 780*640*540mm



Model:12EX-QXD23 30.75.02.01.003

Tilt Bucket 23°

-Replace the standard digging bucket with a mini-excavator tilt bucket according to job requirements.
-The tilt bucket allows for altering the angle of the bucket without the need to adjust the position of the excavator, enabling efficient operation.
-This reduces mechanical wear and fuel consumption, thereby improving work efficiency.
-Packaged Weight: 75.5KG
-Packaged Dimensions: 650*660*465mm



Model:12EX-QXD32 30.75.02.01.002

Tilt Bucket 32°

-To replace the standard bucket for microexcavation according to the job requirements
-The tilting bucket can change the tilting angle of the bucket without the need to change the position of the excavator, enabling efficient operation.
-It reduces mechanical wear and fuel consumption, thereby enhancing operational efficiency.
-Packaged Weight: 84.8KG
-Packaged Dimensions: 840*660*465mm



Model:12EX-QXD39.4 30.75.02.01.004

Tiltchng Bucket 40°

-To replace the standard bucket for microexcavation according to the job requirements
-The tilting bucket can change the tilting angle of the bucket without the need to change the position of the excavator, enabling efficient operation.
-It reduces mechanical wear and fuel consumption, thereby enhancing operational efficiency.
-Packaged Weight: 99.5KG
-Packaged Dimensions: 1140*660*465mm



Model:12EX-HYMZJ II 30.75.02.06.004

Hydraulic Thumb Clamp

-It has an advantage in grasping small wood cylindrical, and strip-like materials when used in conjunction with the bucket.
-A multi-functional bucket clamp developed based on the bucket, capable of digging and clamping, suitable for stone loading and unloading, road maintenance, and other versatile applications, offering ease of operation.
-Packaged Weight: 19.5KG
-Packaged Dimensions: 550*260*250mm



Model:12EX-XZMQ 30.75.02.03.002

Hydraulic Rotation LOG GRAPPLE

- The rotating grapple can perform 360° rotational work
- Fully hydraulic-driven, ensuring precise tool positioning and sturdy structure
- Suitable for light materials such as scrap steel, wood, bales of hay, cotton bales, sugarcane piles, tree branches, domestic waste, as well as floating objects on the water surface operation
- Product Weight: 69.5KG
- Product Dimensions: 810*500*280mm



Model:12EX-ZMQ 30.75.02.03.001

Grapper

- Simple and reliable construction.
- Suitable for light materials such as scrap metal, wood, bales of hay, cotton, sugarcane, branches, household waste, as well as the collection of floating objects on the water surface.
- Packaged Weight: 32.2KG
- Packaged Dimensions: 600*390*340mm



Model:12EX-XZBB 30.75.02.08.001

Hydraulic Rotation Scraper

- Rotating Scraper offers 360° operational rotation
- Fully hydraulic-driven to ensure precise tool positioning and robust structure
- Applicable for land leveling, road scraping, and wall scraping, featuring 360° rotational adjustment for versatile usability
- Product Weight: 43KG
- Product Dimensions: 930*680*250mm



Model:12EX-WD32B 26.049.009.004

Bucket

- Wear-resistant material
- Easy installation and operation, safe and reliable
- Suitable for excavating general clay and handling sand, soil, and gravel
- Packaged Weight: 41.9KG
- Packaged Dimensions: 845*460*280mm



Model:12EX-WD10 30.75.02.01.025

Bucket

- Mainly used for river dredging, clearing water plants, etc.
- Can also be used for construction work such as excavation and sieving, road maintenance, etc.
- Packaged Weight: 26.1KG
- Packaged Dimensions: 310*540*315mm



Model:12EX-WD12 30.75.02.01.030

Bucket

- Mainly used for river dredging, clearing water plants, etc.
- Can also be used for construction work such as excavation and sieving, road maintenance, etc.
- Packaged Weight: 29.7KG
- Packaged Dimensions: 540*370*315mm



Model:12EX-WD15 30.75.02.01.038

Bucket

- Wear-resistant material
- Easy installation and operation, safe and reliable
- Suitable for excavating general clay and handling sand, soil, and gravel
- Product Weight: 25.19kg
- Product Dimensions: 512*420*283mm



Model:12EX-RC 30.08.02.08.003

Brush Cutter

- Mainly suitable for mowing and clearing grasslands, shrubbery, and renovating uneven pastures.
- Easy to use, safe, and reliable
- Product Weight: 112.5kg
- Product Dimensions: 1080*1050*530mm



Model:12EX-AGR 30.33.04.099

Auger Drive Head

- The machine has low energy consumption and delivers effective performance.
- It is easy to use, convenient, and safe
- Suitable for various workites such as drilling holes in electric wire poles, digging tree planting holes, and perforating for photovoltaic installation, where fast drilling is required. Different diameter drill rods can be selected according to actual needs.
- Product Weight: 35kg (Excluding Drill Rods)
- Product Dimensions: 600*200*230mm



Model:12EX-200Adrill 26.073.004.001

200 Auger Drill

- The machine has low energy consumption and delivers effective performance.
- It is easy to use, convenient, and safe.
- Suitable for various workites such as drilling holes in electric wire poles, digging tree planting holes, and perforating for photovoltaic installation, where fast drilling is required. Different diameter drill rods can be selected according to actual needs.
- Packaged Weight: 16.9KG
- Packaged Dimensions: 880*260*250mm



Model:12EX-200Bdrill 26.073.004.003

200 Auger Drill

- The machine has low energy consumption and delivers effective performance.
- It is easy to use, convenient, and safe.
- Suitable for various workites such as drilling holes in electric wire poles, digging tree planting holes, and perforating for photovoltaic installation, where fast drilling is required. Different diameter drill rods can be selected according to actual needs.
- Packaged Weight: 28.3KG
- Packaged Dimensions: 1270*260*250mm



Model:12EX-250Adrill 26.073.004.005

250 Auger Drill

- The machine has low energy consumption and delivers effective performance.
- It is easy to use, convenient, and safe.
- Suitable for various workites such as drilling holes in electric wire poles, digging tree planting holes, and perforating for photovoltaic installation, where fast drilling is required. Different diameter drill rods can be selected according to actual needs.
- Product Weight: 10.7kg
- Product Dimensions: 630*280*270mm



Model:12EX-250Bdrill 26.073.004.004

250 Auger Drill

- The machine has low energy consumption and delivers effective performance.
- It is easy to use, convenient, and safe.
- Suitable for various workites such as drilling holes in electric wire poles, digging tree planting holes, and perforating for photovoltaic installation, where fast drilling is required. Different diameter drill rods can be selected according to actual needs.
- Packaged Weight: 35.1KG
- Packaged Dimensions: 1270*310*300mm



Model:823SS-PF 30.14.10.001

Fork

- There are multiple options available for the length of the fork teeth.
- The equipment can transport items, offering convenience, speed, and wide application in logistics, warehouses, factories, and other settings.
- In practical operation, the fork's lifting capacity must not exceed the host machine's rated load.
- Product Weight: 68.5KG
- Product Dimensions: 1030*650*140mm



Model:12EX-HMZJ 30.75.02.06.002



Model:12EX-300Adrill 26.073.004.006




Model:12EX-300Bdrill 26.073.004.007



Model:M-RC 30.08.02.11.001

Brush Cutter

- Mainly suitable for mowing, clearing bushes, and renovating uneven pastures and meadows.
- Easy to use, safe, and reliable.
- Product Weight: 88.9KG
- Product Dimensions: 1180*1100*450mm



Model: STE35-HK

30.75.03.003

Quick Coupler

The quick coupler for excavators allows for fast installation and interchange of various attachments, such as buckets, rippers, hydraulic breakers, and shears. This capability expands the range of applications for the excavator, saving time and improving efficiency.

-Digital Model Weight: 29KG
-Digital Model Dimensions: 270*200*220mm



Model: 12EX-AGR(C)

30.33.04.099



Model: GQDA-3PT

30.39.06.001



Model: 12EX-ZG

30.75.02.03.003



Model: 12EX-HMR

30.75.02.02.002

Hydraulic Breaker

-Used for road breaking, house demolition, bridge dismantling, and other related applications.

-Product Weight: 65KG

-Product Dimensions: 830*690*330mm



Model: 12EX-HM

30.75.02.02.001



Model: 12EX-HK

30.75.03.010



Model:SSBX42S 30.34.07.001

Skid Steer Wood Chipper
 Model SSBX42
 Fits 18-50 HP Skid Steers
 Rotor Size 21"
 Recommended Material Size 5" dia. (max.)
 Working Pressure (MPa) 17



Model:SSBG060 30.35.12.004

Skid Steer Double scraper grader
 Scraper Working Length:60 3/64"
 Number Of Scrapers: 2pcs
 Scraper Angle: 11.5°
 Weight:552 lbs
 Product Size: 65"×62"×20"



Model:SPA84 30.25.08.001

Skid Steer Bulldozer
 Width: 84"
 Power Required: 30-60 HP
 Angle: 28.5°
 Blade: 1/8"
 Cutting Edge: 7/16"
 Heavy duty adjustable skid shoes
 Universal skid steer quick mount



Model:ECSSTR072 30.45.01.003

Skid Steer Rotary Tiller
 Model ECSSTR072 N.Weight 645.95 lbs
 Working Width 70.86" Measurement
 Total Width 74.80" 84.64"x31.49"x19.29"
 Working Depth 7.08" Working Pressure (MPa) 32-60
 Blade(PCS) 32 Flow 22.45GPM
 Hydraulic Motor BM5-400 Square
 4-hole output shaft 6-φ30"φ26



Model:GB66-SS 30.26.01.004

Skid Steer Grapple bucket
 Model: GB66-SS
 Width 68"
 Height with teeth Closed 28.19"
 Maximum Height with teeth open 47.61"
 Maximum opening 40.36"
 3000# Hydraulic Cylinder (QTY) 2
 Steel Construction of Upper Teeth Hi-strength



Model:SSEFGC175 30.08.05.04.005

Skid Steer flail mower
 Total width: 71"
 Working width: 57"
 Cutting capacity: up to 2"
 Hydraulic flow: 11~15 GPM
 Working Pressure (MPa): 17
 Number of Knives: 28



Model:SSRC72 30.08.02.05.010

Skid Steer Brush Cutter
 Model RC72 Working Pressure(MPa) 17
 Working Width 67.91" Flow(L/min) 45-60
 Cutting Height 1.57"
 Blade(PCS) 2
 Weight 780.43lbs
 Measurement 77.95" x 74.80" x 18.50"



Model:HDRC72 30.08.23.04.001

Skid Steer heavy duty Brush Cutter
 Model HDRC72 Working Pressure(MPa) 35
 Working Width 68.89" Flow(L/min) 75-260
 Cutting Height 1.57"
 Blade(PCS) 3
 Weight 1433lbs
 Measurement 86.61" x 76.77" x 22.83"



Model:HIFRC 30.08.02.07.001

Skid Steer heavy duty Brush Cutter
 5-10" cutting capacity.
 1/4" deck with sides reinforced with 3/8" AR400.
 Piston Motor direct Drive.
 4x bi-directional blades made with 5/8" AR400.
 1/2" double round blade holder.
 Mulching Teeth Standard on all Severe Cutters.



Model:HCRC 30.08.10.01.001

Skid Steer heavy duty Brush Cutter
 Cut Width :74 in
 Cutting Capacity:12 in
 Minimum Cut Height:2 in
 Drive Motor:Piston Motor
 Mounting Type:Universal Skid Steer Plate
 Optimal Operating RPM :1500-1700



Model:BDRC48 30.08.02.06.001

Skid Steer Front Mount Cutter-Adjustable
 Overall Size: L134" x W57" x H21"
 Cutting Width: 48"
 Max. Cutting Capacity: 4" Min. Cutting Height: 2"
 Quantity Of Blades: 2 Flow : 12-16 gpm
 Max Pressure: 3050 psi
 Package Weight: 881.8 lbs



Model:SSVR72 30.50.01.001

Hydraulic Skid Steer Vibratory Roller
 Dimension(LxWdH) : 85 x 32 x 38 in
 Weight : 1620.39 lbs
 Drum Diameter: φ23.4
 Dynamic Force: 37 KN
 Pressure : 6-21 Mpa
 Flow : 16 GPM



Model:ECSSCT72 30.56.02.001

Chain Trencher
 Model: ECSSCT72 Flow (L/min): 45-75
 Digging Depths: 47.24" Trench Widths: 5.11"
 Working Pressure (MPa): 15
 Measurement:78" x 51" x 23"
 Weight:892.87 lbs



Model:SSCM53 30.55.01.001

Hydraulic Skid Steer Concrete Mixer/Bucket mixer
 Model SSCM53
 Maximum volume 0.4m³ Stirring speed (r/min) 30
 Pressure 20Mpa Flow 11-15GPM
 Weight 772lbs
 Length * width * height 850*720*1580mm



Model:SSBM72 30.53.01.001

Hydraulic Skid Steer Broom
 Working width: 72" Number of wafers: 41
 Wafer diameter: 22" Core diameter: 6.5"
 Bucket capacity: 0.8 cubic yard
 Power required: 45-75 HP
 Hydraulic flow: Min. 10 GPM to Max 25 GPM



Model:SSAB72 30.54.01.001

Angel Broom
 Working Width: 72" Number Of Wafers: 41
 Brush Diameter: 27" Core Diameter: 8"
 Sweeping Width At 30° Angle: 63"
 Maximum Angle (left And Right): +/-30°
 Hydraulic Flow: Min. 10 Gpm To Max 25 Gpm
 Do Not Use High-flow



Model:SSECAG-Y 30.33.03.001

Hydraulic Skid Steer Auger
 Flow Rating:5-17 GPM Max Pressure: 2250 PSI
 Drilling Depth:48" Overall Length:80"
 Mount Type:Universal Mounting Plate Heigh:20"
 Mounting Plate Width:48"



Model:SSECAG-Y 30.33.03.001

Hydraulic Skid Steer Auger
 Flow Rating:5-17 GPM Max Pressure: 2250 PSI
 Drilling Depth:48" Overall Length:80"
 Mount Type:Universal Mounting Plate Heigh:20"
 Mounting Plate Width:48"



Model: SSECAG-Y 30.33.03.003

Hydraulic Skid Steer Auger

Drill Bits: 6" 12" 14"
Working Pressure (MPa): 14
Flow (L/min): 32-45
N.Weight: 489.42 lbs
Measurement: 49.21" x 31.49" x 23.62"



Stump Grinder



Hydraulic Grapple



Model: BH01 30.24.01.001

Bale Huger

Round bale handler with universal skid steer mounts.
Constructed of pipe to minimize the risk of puncturing your wrapped bales.
It handles bales with a diameter of 4' to 5' and features a single 2.5" cylinder to provide the strength needed to handle wet bales.



Model: SSHH-680A 30.49.01.002

Skid Steer Hydraulic Hammer

Operating weight: 550 lbs
Working pressure: 1600-2500 psi (110-140 bar)
Working flow: 9.5-16 GPM (36-60 L/min)
Impact rate 500-900 BPM Impact energy 600 joule
Chisel diameter: 2.7" (68mm) Hydraulic hose diameter: 1/2"
Ear spacing - inside/outside: 10.2" (258mm)/11.4" (290mm)
Pin center to center: 8.8" (224mm)



Model: SSHH-750A 30.49.02.002

Skid Steer Hydraulic Hammer

Working weight: 1000 lbs
Working pressure: 1700-2500 psi (120-170 bar)
Working flow: 13-24 GPM (50-90 L/min)
Impact rate 500-800 BPM Impact energy 785 joule
Chisel diameter: 3" (75mm)
Hydraulic hose diameter: 1/2"



Model: PD680-PZ 30.49.03.001

Skid Steer Hydraulic Hammer

Operating weight: 1100 lbs Energy Class: 680 ft.-lbs
Oil Flow: 9.5-16 gpm
Working Pressure: 1600-2000 psi
Chisel Shaft Diameter: 2.7" Blow rate: 500-900 bpm
Domed cup inside diameter: 8"
Hydraulic hose diameter: 1/2"



Model: PD750-PZ 30.49.04.001

Skid Steer Hydraulic Hammer

Operating weight: 1100 lbs Energy Class: 680 ft.-lbs
Oil Flow: 9.5-16 gpm Shipping weight: 1146.4 lbs
Working Pressure: 1600-2000 psi
Chisel Shaft Diameter: 2.9" Blow rate: 500-900 bpm
Domed cup inside diameter: 8"
Hydraulic hose diameter: 1/2"
Packaging size: 56.7" x 53.54" x 31.5"



Model: SSSCR72 30.57.01.001

Skid Steer Soil conditioner

Overall Width : 75in
Working Width: 72in
Blade : 76 pcs
Flow range: 18-23 GPM
Flow pressure: 2900 psi
Drive direction: forward/reverse



Model:ECSSSTG200 30.58.01.002

Skid Steer Stump Grinder

Above Ground Grinding Height: 21.5"
Below Ground Grinding Height: 19"
Cutting Teeth: 16 Cutting Wheel Diameter: 24"
Cutting Wheel Thickness: 3/4"
Cutting Wheel Speed: 1,100-1,350 RPM
Hydraulic Flow: 14-25 GPM
Hydraulic Pressure Required: 2,320-3,000 PSI



Model:ECSSLR72 30.59.01.002

Skid Steer Landscape Rake

Working Width: 72" Number Of Racks: 12
Bucket Capacity(m³) : 0.4
Total Number Of Teeth: 456 Flow (L/min): 60-120
Working Pressure (MPa): 14-20
Weight: 1929.04 lbs
Measurement: 83" x 66" x 42"



Model:ECSSRB 30.60.01.003

Skid Steer Tree Shears

Model: ECSSRB
Maximum cutting size: 15.74in
Weight(KG): 700
Measurement: 46.46*36.22*47.48in
WorkingPressure(MPa): 20



Model:SSFM81 30.62.003.001

Forestry Mulcher

Product Height: 66" (w/push bar), 43" (w/o push bar)
Minimum Loader Power Required: 75HP
Cut Width: 61"
Cut Capacity: 8" Diameter
Rotor Diameter: 12" (w/o teeth), 24" (w/teeth)
Flow (L/min): >110
Maximum Pressure: 3045 Psi



Model:SSDFM60 30.64.003.001

Disc Mulcher

Cutting Width(MM): 1520
Stubble height(mm): 40
Number of blades(PCS): 50
N Weight(KG): 820
Measurement(MM): 2020*1970*880
WorkingPressure(MPa): 35
Flow(l/min): 75-260



Model:SSSG72 30.35.33.001

Skid Steer Grader

Model: SSSG72
Height Adjust: ± 5.9 in Hydraulic Angling: ± 26°
Hydraulic Tilt: ± 15° Working Width: 72"
Swing Angle Up And Down: 35°
Swing Angle Left And Right: 25°
Working Pressure (MPa): 20
Skid Steer Interface Dimensions: 45" x 16"



Model:4IN1BCT 30.68.04.001

4 IN 1 Bucket


Overall Width: 75 in Overall Height: 32.2 in
Overall Length: 74.5 in Open distance: 35.4 in
Pressure 16-21 Mpa Capacity: 0.5 m3
Suitable Flow (L/min): 50~120 Packing Information
One unit per plywood case
Packing Dimensions: 78.8"x 37.5"x 32.7"
Weight: 970 lbs



Model:SSDH-5 30.32.07.01.001

Skid Steer Disc Plow

Frame Width: 78"
Disc Height: 20"
Weight: 890lbs
Discs: 20 set



Model:SSSB165 30.22.05.001

Skid Steer Stone Burier/ Soil Cultivator

Number of blades: 32 Tilling width: 63"
Tilling depth: 4.75" HP required: 35-50 hp
Rotor speed: 208 rpm
Hydraulic flow: 16-21 GPM
Auxiliary pressure: 2900 PSI



Model:SSRPB80 30.73.01.001

Skid Steer Rock Picker Bucket
 Motor: Cycloid Motor
 Working Width: 78 in
 Working Pressure (MPa): 17
 Flow (L/min): 60-100
 Maximum Speed of Picking Up Stones (r/min): 62
 Min. Picking Stone Diameter: 1 9/16"



Model:BRT30TSS-CY 31.03.115

Skid Steer Firewood Processor
 Power source: Tractor or skid steer
 Min. Power (HP): 35 Splitting force (T): 30
 Max length of feeding wood (mm): 6000
 Diameter of feeding wood (mm): 450
 Max length of splitting wood (mm): 580
 Max diameter of splitting wood (mm): 450
 Operation control: Remote Control
 Wedge: 4-way with manual adjustable



Model:BRT30TSS 31.03.114

Skid Steer Firewood Processor
 Rotating speed of chainsaw (rpm): 10000
 Mini time of sawing down (s): 3
 Adjustable height of wedge (mm): 150
 Control valve: Remote Control Panel
 Ram speed / hydraulic cycle (s): 3
 Ideal Productivity: 12 cbm/hour 3 cord/hour
 Package size (L*W*H, mm): 2150*1230*1120
 N/G. Weight (kg): 600/640



Wood Cleaver



Stone Bucket



Snow Blower



Bucket Mixer



Digger



Backhoe



Model:M-BK32 26.049.012.002

Model:M-BK45
Bucket 32" / Bucket 45" 26.049.012.001

- This equipment is compatible with skid steer loaders or compact loaders.
- It is primarily used for shoveling, loading, unloading, and transporting loose materials such as soil and gravel, and can also perform light excavation work on rocks and hard soil.
- Product Weight: 58KG
- Product Dimensions: 830*665*383mm



Model:M-CT 30.56.03.001

Trencher

- This product is a continuous trencher, which can be adapted to skid steer loaders.
- It is mainly used for trenching, slotting, and laying underground agricultural pipelines, urban and rural optical cables.
- The trenching depth is adjustable, making it suitable for various types of operations.
- Product Weight: 117KG
- Product Dimensions: 1590*820*830mm



Model:M-HGB 30.26.12.001

Grapple

- This machine is suitable for skid steer loaders or compact wheel loaders. It is designed for handling light materials such as scrap metal, wood, bales of hay, cotton bales, sugarcane piles, branches, household garbage, as well as floating debris on the water's surface.
- Packaged Weight: 174KG
- Packaged Dimensions: 1010*830*780mm



Model:M-AG 30.33.04.002

Auger

- Mechanical energy consumption is low, with effective performance.
- Easy to use, safe, and reliable
- Suitable for various working conditions such as drilling holes in wire poles, tree planting, and photovoltaic cable routing, where rapid drilling is required.
- Packaged Weight: 136KG
- Packaged Dimensions: 1730*700*560mm



Model:M-DRG 30.37.002

Mini Single Arm Digger

- Suitable for mini skid steer loaders
- Easy to use, safe, and reliable
- This machine is suitable for excavating trenches, laying pipelines, etc., and is applicable for construction and production operations in transportation, municipal landscaping, greening, farmland, water conservancy, and other fields.
- Packaged Weight: 128KG
- Packaged Dimensions: 1990*680*540mm



Model:M-BKM 30.55.03.001

Mini Concrete Cement Mixer

- Suitable for mini skid steer loaders
- Convenient to use, safe and reliable
- The concrete mixing bucket integrates the functions of a mixer and a bucket, reducing the hassle in shoveling and transporting sand and stones, thereby improving work efficiency.
- The hydraulic drive mechanism enables the mixer to rotate forward and reverse, accelerating the uniform mixing of the concrete.
- Packaged Weight: 199KG
- Packaged Dimensions: 1040*760*740mm



Model:M-HMR 30.49.05.002



Model:M-AB 30.54.01.004

Sweeper

- The main object of the snow sweeper is natural loose accumulated snow. It is equipped with a front-mounted large-diameter polypropylene and steel wire mixed brush roller, known for its wear resistance, elastic bending resistance, and not causing damage to the road surface.
- The hydraulic drive enables the snow sweeper brush roller to turn left and right, with an adjustable steering angle within the range of ±30°, thereby altering the snow.
- The brush roller can sway left and right along the transverse slope of the road, enhancing the snow removal effectiveness, maintaining uniform contact between the brush filament and the road surface, resulting in evenly distributed wear and improved brush roller lifespan.
- Product Weight: 180KG
- Product Dimensions: 1650*1300*650mm




Model:M-BM 30.53.01.004

Sweeper With Bucket

- It adopts hydraulic drive, realizing bi-directional sweeping, and the bottom of the bucket is equipped with replaceable wear-resistant plates to extend the service life of the bucket body.
- The brush uses a new type of mixed fiber brush, wherein the plastic filaments are made of high elastic, wear-resistant polypropylene engineering materials, and the steel filaments are made of high elastic, wear-resistant material 32S(MnTi), improving the service life and sweeping effect of the brush.
- Unique anti-rollover design can effectively prevent excessive overturning of the cover and damage to the cab.
- Product Weight: 290KG
- Product Dimensions: 1610*1300*560mm



Model							
TLMB5	850-970	1300	160	18-25	16	85	1340*720*60
TLM105	1050-1170	1200	160	15-25	20	105	1240*720*60
TLM115	1150-1370	1300	160	18-25	20	115	1340*720*60
TLM125	1250-1575	1400	160	20-35	24	125	1440*720*60



Model									
TXG32	720	880	180	20-36	18	540	131	950*540*560	
TXG48	950	1110	180	20-36	24	540	147	1180*649*580	
TXG64	1180	1340	180	20-36	30	540	165	1410*649*580	
TXG56	1410	1570	180	20-36	36	540	179	1640*649*580	



Model							
TW105	1050-1170	1150	100	15-40	20	105	1250/770/71
TW125	1250-1370	1350	100	23-40	24	125	1450/770/71
TW145	1450-1570	1550	100	25-40	28	145	1650/770/71
TW165	1650-1770	1750	100	30-40	32	165	1850/770/71



Model								
TS950	1200	1370	160	35-50	38	540	238	1680*610*710
TS968	1400	1670	190	35-60	42	540	246	1680*610*730
TS986	1600	1770	190	35-50	48	540	270	1680*610*710
TS984	1800	1970	190	35-50	54	540	290	2060*610*710
TS981	2000	2170	190	35-60	60	540	321	2280*610*710



Model										
TA100	1950	1170	200	30-40	30	540	230	1320*800*750		
TA120	1250	1370	200	35-50	36	540	250	1520*800*750		
TA140	1450	1570	200	40-60	42	540	275	1720*800*750		
TA160	1650	1770	200	45-60	48	540	285	1920*800*750		
TA180	1550	1970	200	50-80	54	540	310	2120*800*750		



Model										
KK-4	1190	1441	130	30-50	36	640	266	15307.749e7		
KK-5	1300	1641	130	30-50	42	640	270	17307.749e7		
KK-6	1690	1941	130	40-50	54	640	364	20350.749e7		
KK-7	2070	2316	130	40-63	66	640	348	23350.749e7		



Model							
TH125	1150	1350	220	35-60	36	540	1470/800/790
TH145	1360	1990	220	35-60	42	640	1670/800/790
TH165	1560	1790	220	40-60	48	640	1870/800/790
TH185	1750	1990	220	45-60	54	540	2070/800/790
TH205	1960	2190	220	50-60	60	540	2270/800/790



Model								
TU155	1600	1710	220	45-80	36	540	437	1850*300*80
TU180	1800	1950	220	50-80	42	540	436	2100*300*80
TU205	2100	2210	220	60-80	48	540	544	2350*300*80
TU230	2300	2400	220	70-80	54	540	621	2600*300*80



Model										
RXQUG200	2000	2140	200	60-90	60	540	446	2200*750*71		
RXQUG220	2200	2330	200	60-90	66	540	456	2280*750*71		
RXQUG240	2400	2520	200	60-90	72	540	491	2680*750*71		



Model:TB Series

Model								
TB155	1500	1730	270	45-150	36	540	543	1750*950*915
TB180	1850	1900	270	50-150	42	540	515	2000*950*915
TB205	2100	223	270	60-150	48	540	686	2400*950*915
TB230	2350	2400	270	70-150	54	540	745	2700*950*915



Model:EFM Series

Model	Horsepower (HP)	Blades Number	Working width (mm)	Cutter pitch (mm)	Input speed (r/min)	Weight (Kg)	Size (mm)
EFM01	20-40	11	900	47	540	200	800*950*1685
EFM11	30-60	24	1100	47	540	280	800*950*1285
EFM111	30-60	24	1100	47	540	280	800*950*1485
EFM111	40-80	30	1200	47	540	320	800*950*1885
EFM111	40-80	30	1200	47	540	340	800*950*2085



Model:BCRL Series

Model	Horsepower (HP)	Blades Number	Working width (mm)	Cutter pitch (mm)	Input speed (r/min)	Weight (Kg)	Size (mm)
BCRL11	30-60	24	1100	47	540	310	1600*1200*1495
BCRL11	30-60	24	1100	47	540	330	1600*1200*1695
BCRL11	40-80	30	1100	47	540	350	1600*1200*1895
BCRL11	40-80	30	1100	47	540	370	1600*1200*2095



Model:EFGC Series

Model	Horsepower (HP)	Blades Number	Working width (mm)	Cutter pitch (mm)	Input speed (r/min)	Weight (Kg)	Size (mm)
EFGC121	30-60	24	1200	42	540	290	800*950*1565
EFGC131	30-60	24	1300	42	540	300	800*950*1665
EFGC141	40-80	24	1400	42	540	310	800*950*1765
EFGC151	40-80	24	1500	42	540	320	800*950*1865
EFGC161	40-80	24	1600	42	540	330	800*950*1965
EFGC171	40-80	28	1700	42	540	340	800*950*2065
EFGC181	40-80	28	1800	42	540	350	800*950*2165
EFGC191	50-75	30	1900	42	540	360	800*950*2265



Model:EFGCH Series

Model	Horsepower (HP)	Blades Number	Working width (mm)	Cutter pitch (mm)	Input speed (r/min)	Weight (Kg)	Size (mm)
EFGCH01	30-60	24	1300	42	540	350	800*950*1865
EFGCH11	40-80	24	1300	42	540	370	800*950*1965
EFGCH21	40-80	24	1400	42	540	380	800*950*2065
EFGCH31	40-80	28	1700	42	540	390	800*950*2165
EFGCH41	50-75	30	1900	42	540	410	800*950*2265



Model:EFME Series

Model	Horsepower (HP)	Blades Number	Working width (mm)	Cutter pitch (mm)	Input speed (r/min)	Weight (Kg)	Size (mm)
EFME151	30-60	24	1300	42	540	330	800*950*1665
EFME151	40-80	24	1400	42	540	350	800*950*1865
EFME171	40-80	28	1700	42	540	370	800*950*2065
EFME191	50-75	30	1900	42	540	390	800*950*2265



Model:MFZ Series

Model	Horsepower (HP)	Blades Number	Working width (mm)	Cutter pitch (mm)	Input speed (r/min)	Weight (Kg)	Size (mm)
MFZ121	30-60	24	1100	72	540	365	800*950*1965
MFZ131	40-60	24	1200	72	540	385	800*950*1965
MFZ171	40-60	28	1700	72	540	485	800*950*2565
MFZ201	50-75	30	1900	72	540	425	800*950*2265



Model:SB Series

Model							
	mm	mm	HP			KGS	
SB105	970	1325	20-26	20	540	302	1410*1430*900
SB125	1180	1525	25-30	24	540	324	1610*1430*900
SB145	1390	1715	30-40	28	540	348	1810*1430*900
SB165	1590	1905	35-45	32	540	372	2010*1430*900



Model:BB Series

Model	Working width (mm)	Total blade height (mm)	Side panel height (mm)	Power (HP)	Blades (PCS)	N.Weight (KG)	Measurement (mm)
BB40C	1225	1227	210	20-25	4	150	1250*900*210
BB50C	1525	1527	210	20-25	5	170	1550*900*210
BB60	1825	1827	210	20-25	6	210	1850*900*210
BB70	2125	2127	210	20-25	7	250	2150*900*210
BB80	2425	2427	210	20-25	8	290	2450*900*210



Model:AGT-JT-TFPE-75 31.06.005

Traffic Cones

Model: JT-TFPE-75
Color: tangerine/red
Material: PE
Reflective film: Reflective Tape 250mm or 100mm+100mm or oem
Product name: PE cone pe traffic cone
road work cones 75cm traffic cones safety sign PE traffic cone
Product Size 75cm black bottom seat
L*V*H 37*37*75cm; 2.5KG



T-TOP BOLLARD & BASE
100 PCS

ORANGE BUNTING
1500 METRE

Model:AGT-JT-TTP-1100 31.06.010

Column-colorful flag combination

Model: JT-TTP-1100
Color: fluorescent red
Material: PE column + PVC base
Reflective film: Reflective Tape 240mm or 100mm+100mm
Product Name: PE warning post T-TOP BOLLARD&BASE
1100mm Road Delineator Post T Top Bollards
Product Size 110CM
column : L*W*H 20*20*110cm 0.8KG
Base: L*W*H 42*42*5cm 8KG



Model:ATK-B1000 30.78.01.002

Two post Base plater Auto lift /asymmetric

1. Symmetric telescoping reach arms provide versatile support positions.
2. Heavy-duty structural column with extra-large base to increase stability.
3. 10,000 lbs capacity.
4. Maximum lifting height: 72".
5. Maximum working width: 100".
6. Minimum height: 4-11/2".
7. Two-point manual lock release.
8. Hydraulic power unit.



Model:ATK-TC24 31.07.003

Tire Chop Machine

1. Classic horizontal swing arm.
2. Self-centering four-jaws with dual pneumatic cylinders for rim clamping.
3. Turntable clockwise and anti-clockwise rotation.
4. Step pedal control operation.
5. Plastic jaw cover for all wheel contact points.
6. Air regulator and oil lubricator.
7. Plastic protection mount/dismount head.



Model:ATK-WB24A 31.07.010

Tire balancer

Rim Diameter: 10"-24"
Rim Width: 1-1/2"-16"
Balancing Speed: 220RPM
Maximum Wheel Weight: 154lbs
Accuracy: 1g (0.0023oz)
Voltage: 115V / 60HZ 8A
Maximum Tire Diameter: 30-3/8"



Model:AGT-ST3065V 31.10.020

Tent 306515ST (ST3065V)

Series Number: ST3065V
Size: 114' 17" x 29' x 45' in
Weight: 2535.31 lbs
Sail Material: PVC
Roof Style: Peak Roof Style Truss Frame



Model:AGT-ST4040C 31.10.023

Tent 4040CST (ST4040C)



40Ft x 40Ft / 12m x 12m
4040 Peak Roof Customer Shelter
4040 Peak Roof Customer Shelter



Model:AGT-ST4080V 31.10.021

Tent 4080CST(ST4080V)

Product Feature: High strength, easy assemble and dismantling, large capacity, excellent stability.
This product can be easily installed and removed and can be used anywhere, anytime.
Package: Metal Box with Customer's Labels Beautiful and firm, conducive to handling, rustproof, waterproof and fireproof.Part Bag Bolts, Rope, Steel Wire and manuals



Model:HPW3650 31.05.01.001

Hot water cleaning machine

Pressure range: 3500-4000 PSI
Flow rate: 4.0 GPM
300,000 BTU per hour
Temperature rises to 85 °C in 1.5 minutes (average)
High pressure hose: 32'
Five quick coupler nozzles: 0°/15°/25°/40° and one soap
Downstream soap injection system
Water supply: Tap water



Model:AGT-CPD35

CPD35-NI/NF battery forklift



Model:AGT-CBD15-E1C2

Electric Pallet Trucks



Model:AGT-NTS-ST


Double use for tractor and skid steers



Model:SAH100-2

30.14.01.002

COM-JDCPF JD Compact Pallet Fork Frame
Fork Length 48"
Overall Length 58"
Width 5.9"
Height 39"
Hitch SS, JD, EG



Side-shift fork



Model:AGT-EX726

30.14.09.001

Forklift sleeve (extended fork sleeve) EX726
Extended Length:1830mm / 72.04"
Suitable For Fork Width:150mm / 5.90"
Minimum Applicable Fork Length:1220mm / 48.03"
Weight:64kg / 141.09



Model:T35A

Off-road forklift truck



Model:T50A

Off-road forklift truck



Model:T60A

Off-road forklift truck



Model:HPW4000 31.05.01.001

Hot water cleaning machine

Pressure range: 3500-4000 PSI
Flow rate: 4.0 GPM
300,000 BTU per hour
Temperature rises to 85°C in 1.5 minutes (average)
High-pressure hoses: 33'
Five quick coupler nozzles: 0°/15°/25°/40° and one soap
Downstream soap injection system
Water supply: Tap water



Model:10FWIF24 31.10.060

10FT



Model:10FWIF24 31.10.060

10FT



Model:BGS Series

Model	Working width (mm)	Total width (mm)	Side panel Height (mm)	Power (HP)	Blades (PCS)	W. Height (mm)	Measurement (mm)
BGS-648	1200	1335	326	16-33	4	218	1450*1300*450
BGS-680	1600	1635	326	25-45	6	259	1680*1300*450
BGS-872	1800	1935	326	25-45	6	259	1680*1300*450
BGS-884	2100	2235	326	25-45	7	323	2280*1300*450



Model:BX52G 30.34.05.001

Wood Chipper

3-Point Hitch CAT 1 PTO Shaft RPM:540 RPM (1000 temp possible)
Length Of PTO Shaft:27inch Drive system Direct Drive
Tractor Engine Power Recommended:18-50hp / 13-37kw
Power Needed For Max. Performance:30-40hp
Rotor Diameter:23 inch Rotor Width:0.63inch + winglets
Rotor Weight:143lbs Dimensions (HxWxD):54x58x72 inch
Total Weight:452 lbs Number Of Knives:4 + 1
Length Of Rotor Knife:8.2 inch
Counter Knife Adjustment Range:0 ~ 0.2 inch



Model:NTSD-7 31.03.003.002

No-Till Seeder-7

7" Spacing
Spring Loaded Double Disc Opener
Disc Scrapers
Divided Stainless Steel Hopper
Standard Seed/Fertilizer seedcups on front and rear
Full width Cage Roller
Compaction scrapers
Rear Roller



Busy at both ends